

Abrasive sponge, flexible, coated on 1 side

SW 510



Properties

Grain	Aluminium oxide
Coating	Close

Product benefit

Thin, ultra flexible sanding sponge for particularly hard-to-reach areas such as indentations, profiles and edges - Tight foam structure, allowing for exceptionally uniform pressure distribution and an extra fine finish - No bending, no creases - Can be used wet and dry

Application

Paint/Varnish/Filler	●
Wood	●
Plastic	○
Metals	○

Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------

Width x Length x Height	Density	grain	Density	Grit color	Foam color	Article number
4-1/2 x 5-1/2 x 3/16	hard	100	hard	white	gray	303588
4-1/2 x 5-1/2 x 3/16	hard	180	hard	white	gray	303589
4-1/2 x 5-1/2 x 3/16	hard	220	hard	white	gray	303590
4-1/2 x 5-1/2 x 3/16	hard	280	hard	white	gray	303591
4-1/2 x 5-1/2 x 3/16	hard	320	hard	white	gray	337849

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de

