
Abrasive cloth, waterproof

CS 416 Y





Properties

Bonding agent	Resin
Grain	Zirconia alumina
Coating	Semi-open
Backing	Y-polyester

Product benefit

Very high aggressiveness and abrasive performance - Long service life also when used on materials that cause clogging

Materials

Stainless steel	●
Plastic	●
NF metals	◑

Applications

- Railing construction
- Wall and façade builder
- Apparatus and container manufacturing
- Foundries

Available grits:

16 | 24 | 30 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 | 3000

Width x Length	grain	type of joint	type of coat.abras.	Article number
7-7/8 x 29-1/2	24	F7G sine joint	CS 416 Y	307073
7-7/8 x 29-1/2	36	F7G sine joint	CS 416 Y	307074
7-7/8 x 29-1/2	40	F7G sine joint	CS 416 Y	307085
7-7/8 x 29-1/2	60	F7G sine joint	CS 416 Y	307086
7-7/8 x 29-1/2	80	F7G sine joint	CS 416 Y	307087
7-7/8 x 29-1/2	100	F7G sine joint	CS 416 Y	307088

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Width x Length	grain	type of joint	type of coat.abras.	Article number
7-7/8 x 29-1/2	120	F7G sine joint	CS 416 Y	317715

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de