
Diamond cup grinding wheel

DS 600 S *SUPRA*





Properties

Design	Brazed
Segmentation	Standard
Aggression	■■■■■□□
Service life	■■■■■■□

Product benefit

Excellent dust extraction thanks to specially designed (fan-shaped) opening - Low weight thanks to lightweight steel plate - Rugged performance and operation with minimum vibrations

Materials

Concrete	●
Firebrick	●
Natural stone	●
Masonry	●
Brickwork	●

Applications

- ▸ Building construction
- ▸ Floor tilers
- ▸ Concrete plants
- ▸ Natural stone businesses

Diameter x Bore	Cup grinding wheel height [mm]	Vmax m/s	Max. RPM	Segment: Number / Width / Height	Article number
4 x 5/8 / 7/8	20,5	80 m/s	15300 rpm	16 / 5/16 / 3/16	331022
4-1/2 x 7/8	20,5	80 m/s	13300 rpm	16 / 5/16 / 3/16	331023
5 x 7/8	20,5	80 m/s	12200 rpm	16 / 5/16 / 3/16	331024
7 x 7/8	30,5	80 m/s	8500 rpm	24 / 5/16 / 3/16	331025

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de