

Cut-off wheel

A 24 N SUPRA



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■ ■ ■ □ □ □ □
Aggression	■ ■ ■ ■ ■ □ □
Service life	■ ■ ■ ■ ■ □ □

Product benefit

Special recipe prevents smearing and clogging - High removal rate on stainless steel due to hardened aluminum oxide

Materials

Stainless steel	●
Aluminium	◐

Applications

- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Thickness x Bore	Form	Vmax m/s	Max. RPM	Article number
4-1/2 x 3/32 x 7/8		80 m/s	13300 rpm	3020
5 x 3/32 x 7/8		80 m/s	12200 rpm	2951
6 x 3/32 x 7/8		80 m/s	10200 rpm	235377
7 x 1/8 x 7/8		80 m/s	8500 rpm	13469
9 x 1/8 x 7/8		80 m/s	6600 rpm	13477

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

