

Cut-off wheel

A 646 R SUPRA



Fe-S-Cl
<0,1%



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■■□
Aggression	■■■■■■■□
Service life	■■■■■■■□

Product benefit

Free of iron, sulphur and chlorine - Universal use on steel and stainless steel - Cut-off disc made of self-sharpening, calcined aluminum oxide - Tremendous aggressiveness when used for cutting solid steel materials

Materials

Steel	●
Stainless steel	○

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop
- Stainless steel processing industry
- Railing construction

Diameter x Thickness x Bore	Form	Vmax m/s	Max. RPM	Article number
4-1/2 x 1/16 x 7/8	— —	80 m/s	13300 rpm	340947
5 x 1/16 x 7/8	— —	80 m/s	12200 rpm	340946
6 x 1/16 x 7/8	— —	80 m/s	10200 rpm	340945

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

