Cut-off wheel
EDGE SPECIAL





Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■
Aggression	■■■■■■□
Service life	■■■■■■

Materials

Stainless steel	●
Steel	●

Product benefit

Short cutting times and long service life - Low burr formation - Low thermal load - 25 pieces delivered in the Kronenflex® tub for long-lasting high performance and moisture protection

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop
- Stainless steel processing industry
- Railing construction
- Oil and gas industry
- Pipeline construction

Diameter x Thickness x Bore	Form	Vmax m/s	Max. RPM	Article number
4-1/2 x .045 x 7/8	▬	80 m/s	13300 rpm	317818
4-1/2 x .045 x 7/8	⌒	80 m/s	13300 rpm	317819
5 x .045 x 7/8	▬	80 m/s	12200 rpm	317820
5 x .045 x 7/8	⌒	80 m/s	12200 rpm	317821

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Thickness x Bore	Form	Vmax m/s	Max. RPM	Article number
6 x 1/16 x 7/8		80 m/s	10200 rpm	317822
6 x 1/16 x 7/8		80 m/s	10200 rpm	317823

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de