

Cut-off wheel INOX

Z 960 TX SPECIAL



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Zirconia alumina
Bond	■■■■■■■■
Aggression	■■■■■■■■
Service life	■■■■■■■■

Product benefit

Free of iron, sulfur and chlorine - Ideal for tough/hard materials such as titanium and high-alloy steels - Short cutting times and long service life due to self-sharpening zirconia alumina - Low thermal load - Low burr formation - 25 pieces delivered in the Kronenflex® tub for long-lasting high performance and moisture protection

Application

Stainless steel	●
Alloys	●
Carbon steel	●
Titanium	●

Target group

- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Thickness x Bore	Form	Vmax m/s	Max. RPM	Article number
4-1/2 x 3/64 x 7/8		80 m/s	13300 rpm	325292
4-1/2 x 3/64 x 7/8		80 m/s	13300 rpm	322184
5 x 3/64 x 7/8		80 m/s	12200 rpm	325293
5 x 3/64 x 7/8		80 m/s	12200 rpm	322185

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

